

ASSEMBLY FOR TREATING BLOOD VESSELS AND  
A METHOD THEREFOR

This invention relates to an assembly for the treating of blood vessels and more specifically to an assembly for the replacing of and/or covering up of damaged, blood vessel inner layers and to a method therefor.

5 An often occurring medical problem is the silting up of blood vessels with for instance calcium, so-called arteriosclerosis. Because of this, a blockage of the blood vessel occurs, so-called stenosis.

10 Stenosis of blood vessels which leads to a narrowing and, in some cases, complete blocking of the blood vessel can lead to dangerous consequences for the patient. Circulatory problems and a deterioration in health can ensue. Advanced stenosis, if not operated upon, can cause wastage and death of body tissue, necessitating, in certain  
15 instances, in amputation.

A known procedure for unblocking blood vessels, 'End artery ectomy', is to separate the inner layer of the blood vessel, the so called tunica-intima, from the blood vessel wall, to cut through and sever the tunica-intima over  
20 the blocked length of the bloodvessel and then to remove the tunica-intima plus blockage from the body. A new tunica-intima then grows back to replace this removed tunica-intima.

A problem here is that this new tunica-intima, the  
25 so called neo-tunica-intima has the tendency to undergo restenosis, i.e. to silt up again, at a quicker rate than the original tunica-intima.

Another problem is that the original tunica-intima is usually separated from the blood vessel wall upto a  
30 distance just past where it is to be severed. Hence on removal of the original tunica-intima, a small piece of this is left hanging loosely in the blood stream, a factor which can cause and hasten the restenosis of the blood vessel.

2

A blood vessel which is particularly susceptible to stenosis is the artery between the groin and the knee.

It is an object of the present invention to obviate at least one of these problems. To this end there is provided, according to a first aspect of the present invention, a blood vessel treating assembly comprising:

- an artificial blood vessel inner layer such as an artificial tunica-intima or the like for replacing a section of blood vessel inner layer previously removed from the blood vessel and/or for covering a predetermined length of damaged blood vessel inner layer, wherein said artificial blood vessel inner layer is associated with the existing blood vessel in such a way as to substantially withhold any loose parts of the blood vessel from obstructing the stream of blood through said blood vessel, and

- introducing means for introducing the artificial blood vessel inner layer into the blood vessel.

In this way an artificial new tunica-intima to replace the old tunica-intima over the removed length thereof and which prevents the re-growing of a natural 'neo-tunica-intima', can be introduced into a blood vessel, to just past the piece of loose hanging original tunica-intima left after removal of a section of the original tunica-intima for instance, this artificial new tunica-intima made of such material as to cause a minimum of restenosis of the blood vessel to occur and which pushes the old loose hanging piece of left behind tunica-intima back against the blood vessel wall where it re-grows onto the blood vessel wall and thus no longer flaps about in the blood stream.

According to a second aspect of the present invention there is provided an artificial blood vessel inner layer, such as an artificial tunica-intima or the like, made of any suitable synthetic material and comprising diameter arranging means for increasing and/or decreasing the diameter of the tube-like section, preferably for use with the above mentioned assembly.

According to a third aspect of the present invention there is provided introducing means for

introducing an artificial blood vessel inner layer, such as an artificial tunica-intima or the like, into a blood vessel, preferably for use with the assembly and/or the artificial blood vessel inner layer as mentioned above.

5           According to a fourth aspect of the present invention there is provided a method of replacing a previously removed inner layer of a blood vessel and/or for covering a predetermined length of damaged blood vessel inner layer comprising the steps of inserting a blood vessel  
10 treating assembly as mentioned above, via an incision, upto a predetermined distance into a blood vessel, increasing the diameter of the artificial blood vessel inner layer to push against the blood vessel walls, whereafter the introducing means are removed and joining the end of the artificial  
15 blood vessel inner layer to the existing blood vessel near the incision.

          According to a fifth aspect of the present invention there is provided a method of increasing and/or decreasing the diameter of a length of artificial blood  
20 vessel inner layer, as mentioned above, or the like, comprising bringing a length of memory metal associated with the artificial blood vessel inner layer to its preprogrammed activation temperature whereafter expansion/contraction of the memory metal effectively increases/decreases the  
25 diameter of the length of artificial blood vessel inner layer.

          According to a further aspect of the present invention there is provided an assembly comprising a tube-like section with at least one length of memory metal  
30 associated therewith, pre-programmed to assume a desired form and/or expand and/or contract at a pre-determined activation temperature, and introducing means for introducing the tube-like section into a passage-like area.

Dr           Further advantages, characteristics and details of  
35 the present invention will become clear from the following description with reference to the accompanying drawings which show:

Figure 1 a perspective partly cut away view of a preferred embodiment of the assembly according to the present invention, during introduction into the artery between the groin and the knee;

5           Figure 2 a partly cut away perspective view of the artificial blood vessel inner layer of the assembly from figure 1;

          Figures 3 to 6 partly cut away perspective views showing the successive steps of the assembly from figure 1  
10 carrying out introduction of the artificial blood vessel inner layer from figure 2, into a blood vessel;

          Figure 7 a partly cut away perspective view of an embodiment of the artificial blood vessel inner layer according to the present invention, when in position within  
15 a blood vessel.

          Figures 8 to 9 partly cut away perspective views of a second embodiment of the present invention.

DE           The assembly 1 (figure 1) is introduced into the artery between the groin and the knee, for example,  
20 preferably via an incision already made for the removal of the original tunica-intima plus blockage.

          This yields the advantage that further incisions for introduction of the assembly into the blood vessel need not be made into the patient, which in turn yields the  
25 benefits of reduced stress on the patient, reduced operation and recovery time and accordingly low hospital costs.

          The assembly 1 comprises an artificial blood vessel inner layer 2 (see figures 2 to 7) and introducing means for introducing the artificial blood vessel inner  
30 layer into the blood vessel.

          The introducing means preferably comprise a catheter-like element 3 (see figures 1, 3-6) which is preferably operated from outside of the body (see figure 1).

          The artificial blood vessel inner layer 2 (figures  
35 2-7), which preferably takes the form of a blood vessel tunica-intima, comprises a tube-like section of synthetic material.

5

A protective cover is preferably associated with the assembly 1, this preferably taking the form of a removeable sheath 4 (figures 3, 4) which extends from the front of the assembly 1 to the catheter operator.

5 This protective sheath 4 ensures that minimal damage is incurred to the blood vessel wall during introduction of the assembly 1 and that the artificial tunica-intima 2 is substantially protected from any possible interferences which could hinder introduction.

10 Diameter arranging means are preferably associated with the tube-like section of synthetic material, said diameter arranging means preferably being a length of preprogrammed memory metal 5 (figures 2-7). These diameter arranging means are often referred to as a "stent".

15 The tube-like section of the artificial tunica-intima 2 is preferably folded over at its leading end (see figures 2-6), the resulting fold 6 of for example 2 cm preferably enclosing the length of memory metal 5 which preferably takes the form of a coil.

20 The artificial tunica-intima 2 is preferably made of a fluoro carbon polymer, by choice the polymer which goes under the name of teflon, a trademarked name, of Du Pont. Clinical tests have shown that teflon is efficient in ensuring a minimum restenosis of blood vessels.

25 The fact that the coil of memory metal 5 is enclosed as it were in the fold 6 of the artificial tunica-intima 2, means that the memory metal 5 does not come into direct contact with either the blood vessel or the blood stream, so that calcium or any other such blood vessel  
30 blocking material is not given a 'foot-hold', on the memory metal, on which it could remain, a factor which further reduces restenosis and/or the rate at which restenosis occurs.

For example, the coil of memory metal can be  
35 preprogrammed to increase from a diameter of about 2 mm at room temperature to a diameter of about 8 mm at a temperature of about 35°C in the blood vessel.

6

In use the assembly is inserted into the blood vessel via an incision already made (see figure 1). A guiding wire (not shown) can be introduced into the blood vessel, before introduction of the assembly 1, whereafter the assembly 1 can be pushed over this guiding wire and through the blood vessel.

Blood vessel widening means, for widening the blood vessel during introduction of the assembly, binging means for blocking off the passage of blood into the assembly during introduction of the assembly into the blood vessel, which could cause introduction complications, and pressure exerting means for pushing the introduced artificial tunica-intima against the blood vessel walls when in position, are preferably associated with the assembly, and preferably take the form of a cone-like element 7 mounted on the front of the catheter-like element 3 (see figures 3-6).

The cone-shape of the cone-like element 7 enables the assembly 1 to easily follow the passage of the blood vessel, pushing the blood vessel walls apart as it goes in order to facilitate introduction of the assembly 1.

During introduction of the assembly 1, the cone-like element 7 is pushed to a point just past where the old tunica-intima was severed so that the fold 6 of the

30 artificial tunica-intima 2 is encircled by the loose hanging remaining piece of the original tunica-intima 8 (see figures 3-7). At this point forward movement of the assembly 1 is stopped.

7

During withdraw of the protective sheath 4, it was found during clinical tests that the artificial tunica-  
5 intima 2 sometimes had the inclination to be pulled back along the catheter-like element 3 together with the sheath 4. In order to prevent this, the catheter-like element 3 can be locally given a somewhat smaller diameter 9 at the position where the memory metal coil 5 is associated with  
10 the fold 6 (see figures 3-6), so that the fold 6 and coil of memory metal 5 remain secured in the desired position on withdrawal of the protective sheath 4.

A short period after withdrawal of the protective sheath the coil of memory metal 5 reaches its activation temperature, whereupon the coil of memory metal 5 increases in diameter and so doing pushes the artificial tunica-intima 25 2 against the walls of the blood vessel (see figure 5).

30           The diameter of the artificial tunica-intima 2 is  
now large enough for the catheter-like element 3, plus the  
cone-like element 7 to be withdrawn out of the blood vessel,  
the cone-like element 7 further exerting a certain pressure  
on the artificial tunica-intima 2 during this withdrawal to  
35 further open out and push the latter somewhat into the blood  
vessel wall (see figure 6).

whole length, whereby unnecessary added pressure is exerted against the blood vessel wall. The artificial tunica-intima, once in place, is held in position by the blood pressure.

After removal of the sheath 4 and the catheter-  
5 like element 3, the artificial tunica-intima 2 can be joined to the blood vessel wall near the incision, preferably by means of stitches. However as shown in figure 7 another possibility to secure the artificial tunica-intima in  
10 position within the blood vessel is to equip the artificial tunica-intima with a further coil of memory metal so that the both ends of the artificial section of tunica-intima are forced against blood vessel wall.

After a period of time the artificial tunica-intima grows onto the original blood vessel wall.

15 It will be obvious that during sterilisation, before introduction of the assembly, the memory metal coil should be temporarily held in its small diameter state, by means of for instance a collar, so that it does not assume its preprogrammed expanded form at this stage.

20 A further embodiment of the present invention is shown in figures 8 and 9.

In this embodiment 20, the length of preprogrammed memory metal, is replaced by a section of gauze-like material 21 (figures 8 and 9), enclosed within an end  
25 section 22 of the artificial tunica-intima.

The end section 22 and artificial intima-tunica are pushed over an expandible balloon 23 and a protective sheath, not shown, is brought thereover. Following introduction, the sheath is removed and the balloon 23  
30 expanded to force the end section 22 against the wall of the blood vessel, whereby it is held in position by the stent 21, to affix with the blood vessel wall. Blood pressure forces the length of unsupported artificial intima-tunica to affix with the blood vessel wall as in the first embodiment.  
35 Following positioning, the balloon 23 is removed.

This stent 21 is preferably made from stainless steel.

9



The artificial tunica-intima is required to be supple, and have elastic and anti-thrombogenic qualities and is preferably porous, in order to mimic the qualities of the tunica-intima. A suitable material herefor is

5 polytetrafluorethylene made by Dacron.

The material for the artificial tunica-intima can be supplied with endothelial cells in order to further enhance its working as a tunica-intima.

Although the present invention refers to the

10 introduction and placing of an artificial intima tunica, intima tunicas from the patient self and from donors may be introduced and arranged in position according to the present invention.

The present invention thus yields a simple yet

15 efficient introduction of a new artificial inner blood vessel layer, which can be carried out in a short time and with a minimum of discomfort to the patient.

The present invention is not limited to the hereabove described and illustrated embodiments, rather

20 within the range of the following claims, a large number of modifications and variations are conceivable.